



MEET+ 100

4K PDAF Camera

For desktop video conferencing and live streaming

Meet+ 100 is a high-quality 4K PDAF webcam. Only one USB(Type-C) cable is used to enable power, control and video. Thanks to being equipped with advanced image processing solution and sensor, it presents realistic color, sharp and smooth image.

Meet+ 100 is developed with Telycam's own-developing focusing algorithm, to make the focus unrivalled fast and accurate. Built-in top-rated quality microphone, it can pick up the voice crystal clearly.

Meet+ 100 is the ideal for desktop video conferencing and live streaming.

4K30 | 69.8°FOV
PRIVACY PROTECTION
PDAF(PHASE DETECTION AUTO FOCUS)




4K sharp image and PDAF(Phase Detection Auto Focus)

The Meet+ 100 utilizes an advanced 4K image processor, a Sony 1/2.55" 12.2MP UHD CMOS sensor, and a 69.8° optical lens, supporting 4K30 and 1080p60 video output. PDAF ensures fast and accurate focusing at short distances.




3X Digital Zoom

Thanks to its true 4K lens, this zoom camera support max 3X digital zoom with crystal video quality. (3x at 1080P)



Flexible USB-A/-C Connection

The webcam features plug-and-play simplicity, equipped with a 1.5-meter dual-ended USB cable (Type-A to Type-C). Firmware upgrades via USB ensure seamless performance, while a built-in high-quality microphone captures crystal-clear audio.



Black Light Compensation

This webcam also support black light compensation, to output always bright and clear image even under low light background.



Security and Privacy Protection

Silicon lens cover help to prevent online hackers from spying on you, and keep the lens clean when the camera not in use.



Specifications

Camera		Meet+ 100
Part Number	TLC-100-U2-4K	
Sensor	1/2.55" 12.2MP UHD CMOS sensor	
Horizontal View Angle	69.8°	
Vertical viewing angle	54.5°	
Diagonal viewing angle	81.5°	
Zoom	1080P supports 3X digital zoom	
EPTZ	Supported	
Output Interface	USB(Type-c)	
Focus	PDAF (Phase Detection Auto Focus)	

Video Format

USB(Type-C)

YUY2:
800*600P15/10;
640*480P30/15/10

MJPG:
3840*2160P30/15/10;
2592*1944P30/15/10;
2048*1536P30/15/10;
1920*1080P60/30/15/10;
1600*1200P30/15/10;
1280*720P30/15/10;
800*600P30/15/10

Image Parameters

White Balance	Auto/Manual
Exposure	Auto/Manual
Flicker	50HZ/60HZ/OFF
2D Noise Reduction	Supported
WDR	Supported
Backlight Compensation	Supported
Mirror, Flip	Supported
Microphone Pointing	Omnidirectional microphone
Sensitivity	-26+2dB RL=2.2KQ Vs=2.0V
S/N Ratio	64dB

General	
Polar Distance	3~5m
Input Voltage	USB power supply
Working Environment	Temperature: -10°C~50°C; Humidity: ≤80%
Webcam Size	76mmxφ48mm
Package Size	114.5mmx87mmx85mm
Net Weight	0.2kg
Gross Weight	0.4kg
Available Color	Dark gray, Silver
Accessories	1.5m USB 2.0(A-C) cable, Manual



Video Output
USB 2.0